



TWINS THAT CARRY ALL



FORLAND C312
3.5 TON CARGO TRUCK

- Turbo Charger + Intercooler
- AC provision
- Competitive price



FORLAND C717
7.5 TON CARGO TRUCK

- Air breaks
- AC provision
- Original cummins engine
- 17 feet deck size

JWForland | JWForland | JWForland | JWForland.com

FORLAND C311 FORLAND C312 FORLAND C717 (CARGO TRUCK)



Regional Office Numbers

Central Region: 0310 3332753 | 0320 3675263

North Region: 0310 3332758 | 0310 3332755

South Region: 0320 0842202 | 0310 3332755

Dealership Office Numbers

Lahore: 0314 4098523 | 0322 4830882

Sahiwal: 0300 9890243 | 0300 9690069

Multan: 0300 7331616 Faisalabad: 0310 3332754

Abbottabad: 0345 9540107 Peshawar: 0333 0550070

Islamabad: 051 2227033 | 0306 5111102

Karachi: 0321 3675261

Line Up		UoM	FORLAND C311	FORLAND C312	FORLAND C717
Dimensions پیمائش	Overall Length	mm	5140	5460	7040
	Overall Width	mm	1960	2000	2265
	Overall Height	mm	2250	2240	2370
	Cargo Length (inner)	mm	3300	3600	5160
	Cargo Width	mm	1810	1900	2060
	Cargo Height	mm	360	360	550
	Tread (F/R)	mm	1533.5/1486	1513.5/1526	1550/1630
	Overhang (F/R)	mm	1120/1420	1120/1540	1140/2100
	Turning Radius	m	6	6.3	7.5
	Ground Clearance	mm	200	185	220
Weight Parameters وزن کابینہ	Frame	mm	192x60x6	192x60x6	192x65x6
	Wheelbase	mm	2600	2800	3800
	Payload	Kg	3000	3500	7500
	Kerb Weight	Kg	2410	2480	3750
	Front Axle	Kg	2000	2000	2600
	Rear Axle	Kg	3000	4000	6500
Engine انجن	G.V.W	Kg	5410	5980	11250
	Model		BJ493ZLQV1	IVQJ3E0LB	Cummins F3.8S3141
	Type		Vertical, inline, water-cooled, four-stroke, turbo charged with intercooler	Vertical, inline, water-cooled, four-stroke, turbo charged with intercooler	Vertical, inline, water-cooled, four-stroke, turbo charged with intercooler
	No. of Cylinders		4	4	4
	No. of valves		8	8	16
	Bore x Stroke	mm	93x102	93x102	102x115
	Compression Ratio		18.2:1	18.2:1	17.2:1
	Fuel type		Diesel	Diesel	Diesel
	Displacement	CC	2771	2771	3670
	Power/RPM		107/3600	107/3600	141/2600
Performance کارکردگی	Torque/RPM	Nm/rpm	280/(1900-2200)	280/(1900-2200)	450/(1300-1500)
	Fuel Tank	Litre	80	100	120
	Gradeability		30%	40%	24%
Transmission دائریسیشن	Maximum Speed	km/h	105	105	92
	Model		5TS32	5TS32	6TS55
	Type		Manual	Manual	Manual
Brake System بریک سسٹم	Drive System		5 Speed	5 Speed	6 Speed
	Gear Ratio		I:5.595 II:2.848 III:1.691 IV:1.000 V:0.794 R:5.347	I:5.595 II:2.848 III:1.691 IV:1.000 V:0.794 R:5.347	I:6.320 II:3.927 III:2.283 IV:1.396 V:1.000 VI:0.789 R:5.858
	Final Gear Ratio (Differential)		5.375	6.167	5.286
Suspension سیسٹم	Clutch		"Diaphragm-spring Clutch 260"	"Diaphragm-spring Clutch 260"	"Diaphragm-spring Clutch 350"
	Front		Hydraulic Drum Brake	Hydraulic Drum Brake	Air Pressure Drum Brake
Steering System	Rear		Hydraulic Drum Brake	Hydraulic Drum Brake	Air Pressure Drum Brake
	Front		Rigid Axle Suspension	Rigid Axle Suspension	Rigid Axle Suspension
Tyre Size	Rear		Rigid Axle Suspension	Rigid Axle Suspension	Rigid Axle Suspension
			Recirculating Ball Type, Hydraulic Power Steering	Recirculating Ball Type, Hydraulic Power Steering	Recirculating Ball Type, Hydraulic Power Steering