

بہترین فیول مائلیج

مضبوط چیسس

شہر کے لئے مفید

پاور سٹیرنگ



2 سال یا
120000
کلو میٹر
وارنٹی*





7.2 فٹ ڈیک



پاور سٹیرنگ



پٹرول انجن



بانیڈرولک بریک

FORLAND
C10
1 TON CARGO TRUCK



| | | |
|---------------------------|---|--|
| Brand | | FORLAND |
| Model | | C-10 |
| Cabin | | 1475 Single Cabin 1475 |
| Seating capacity | | 2 |
| Drive type | | 4*2 |
| Size parameters | Wheelbase mm | 2000 |
| | Cargo box inner parameters (mm) | 2200 × 1410 × 320 (MM) |
| | Overall parameters (mm) | 3860 × 1510 × 1890 |
| | Tread (Front/Rear) (mm) | 1260/1260 |
| Quality parameters | GVW (kg) | 2080 |
| | Load (kg) | 1000 |
| | Curb weight (kg) | 950 |
| Engine | Model | LJ465Q-2AE |
| | Type | Four-cylinder four stroke, in-line, water-cooled, naturally aspirated, multi-point EFI, SOHC |
| | Bore stroke | 65.5x78 |
| | Compression Ratio | 9.3:1 |
| | Displacement (L) | 1.0 L |
| | Valves | 8 |
| | Max. Output (ps/RPM) | 61HP (45kw) /5600rpm |
| | Max. Torque (N.m/RPM) | 85N.M/3500-4000r/min |
| Emissions | Euro IV | |
| Gearbox | Type | MR508A,5MT |
| Clutch (type/size) | | Single dry diaphragm spring ϕ 180 × ϕ 125 |
| Front axle | Load (T) | 1.2T/Non breaking circular pipe beam |
| | Brake specification | Disc hydraulic brake |
| Rear axle | (Load/ratio) | 1.2T/110(5.375) |
| | Brake specification | Drum hydraulic brake |
| Tire (model and quantity) | | 165R13 |
| Frame (size and material) | | 130 × 50 × 4-750 |
| Front Suspension | Type | rigid axle suspension |
| | Number of leaf spring, size and material | 3 |
| Rear Suspension | Type | rigid axle suspension |
| | Number of leaf springs, size and material | 4 |
| Parking brake | | Wheel side hand brake |
| Driving brakes | | Hydraulic brake |
| Power steering | | Electric power assist |