

STRONG RIGID CHASSIS

CITY CONVENIENT

POWER STEERING

FUEL EFFICIENT



2 Years or
WARRANTY*
100,000 KMS

FOODTRUCK




SECURITY TRUCK




LOADING TRUCK





7 Ft Deck



Air duct



40L Fuel Tank



Front Disk Brake

FORLAND
C10
1 L Petrol Pickup



Brand		FORLAND
Model		C 10
Cabin		1475 Single Cabin
Seating Capacity		2
Drive type		4*2
size parameters	Wheelbase mm	2000
	Cargo box inner parameters (mm)	2200 x 1410 x 320 (MM)
	Overall parameters (mm)	3860 X 1510 X 1890
	Tread (Front/Rear) (mm)	1260 / 1260
Quality parameters	GVW (kg)	2080
	Load (kg)	1000
	Curb weight (kg)	950
	Model	LJ465Q-2AE (Petrol)
Engine	Type	Four-cylinder four stroke, in-line, water-cooled, naturally aspirated, multi-point EFI, SOHC
	Bore stroke	65.5X78
	Compression Ratio	9.3:1
	Displacement (L)	1.0L
	Valves	8
	Max. Output (ps/RPM)	61HP (45KW) /5600rpm
	Max. Torque(N.m/RPM)	85M.M/3500-4000r/min
	Emissions	Euro IV
Gearbox	Type	MR508A,5MT
Clutch (type/size)		Single Dry Diaphragm spring 180 x125
Front axle	Load (T)	1.2T/Non breaking circular pipe beam
	Brake specification	Disc hydraulic brake
Rear axle	(Load/ratio)	1.2T/110(5.375)
	Brake specification	Drum hydraulic brake
Tire (model and quantity)		165R13
Frame (size and material)		130x50x4-750
Front Suspension	Type	Rigid axle suspension
	Number of leaf spring, size and material	3
Rear Suspension	Type	Rigid axle suspension
	Number of leaf spring, size and material	4
Parking brake		Wheel side hand brake
Driving brakes		Hydraulic brake
Power steering		Electric power assist